

Dräger Polytron® 3000 Toxic Gas Detection

The Dräger Polytron® 3000 is an intrinsically safe gas detector for the continuous monitoring of more than 60 toxic gases and oxygen in ambient air. It is the part of a new generation of gas detectors developed on a modular platform. Communication to the central control system is done via a 4 to 20 mA signal.



Benefits

Simple, quick installation

The Polytron 3000 consists of two components, the docking station, for mechanical and electrical installation, and the Polytron 3000 transmitter. The docking station can be mounted and wired in advance, guarded against rain and dust by a modular cover until time of commissioning. During commissioning, the Polytron 3000 is simply inserted into the docking station and secured with a quick-quick lock mechanism. After inserting the sensor, the system is ready for operation.

Wide range of applications

With its exceptional electromagnetic compatibility and a variety of mounting options, the CE marked Polytron 3000 is suitable for many different areas of application ranging from chemical to the semiconductor industries.


Easy to operate and maintain

The operation and maintenance of the Polytron 3000 is easy. The tried and tested DrägerSensor is equipped with an integrated data memory that contains all calibration information. This allows the Polytron 3000 to accept a pre-calibrated sensor, speeding up maintenance or sensor change. If preferred, the sensor can be field calibrated in the transmitter.

Explosion Protection

Approvals for worldwide use including, ATEX, IECEx, UL, CSA and temperature range from -40 to +65°C, Protection class (IP66/67).

System Components



ST-3831-2003

Electrochemical DrägerSensor®

Fast response, high accuracy, great stability, long life. Electrochemical DrägerSensors offer all these benefits. You can use the robust and long-life sensors for the selective measurement of the smallest concentrations of toxic gases and oxygen in ambient air.



D-2777-2009

Dräger REGARD® 3900

The Dräger REGARD® 3900 is a standalone, self contained control system for the detection of Toxic, Oxygen and Ex hazards. The control system is fully configurable between 1 and 16 channels, depending upon the type and quantity of input/output boards installed.



ST-335-2004

Dräger REGARD®-1

The Dräger REGARD®-1 is a standalone, self contained single channel control system for the detection of Toxic, Oxygen and Ex hazards. The control system is fully configurable for a single input from either a 4 to 20 mA transmitter or a Dräger Polytron® SE Ex measuring head.



D-6806-2016

Dräger REGARD® 7000

The Dräger REGARD® 7000 is a modular and therefore highly expandable analysis system for monitoring various gases and vapours. Suitable for gas warning systems with various levels of complexity and numbers of transmitters, the Dräger REGARD® 7000 also features exceptional reliability and efficiency. An additional benefit is the backward compatibility with the REGARD®.

Accessories



ST-3805-2003

Dockingstation

For easy and time-saving mounting of the Dräger Polytron 3000 or 7000. One dockingstation is required for each Polytron 3000 or 7000.
Order no. 83 17 990



ST-5676-2006

Viton calibration adapter

Viton adapter for zero-point tests and the calibration of transmitters with electrochemical sensors (not type AC), catalytic sensors (pellistors) and transmitters of type Polytron IR CO₂ and Polytron IR Ex HC.
Order No.: 68 10 536



ST-5678-2006

Gassing adapter

Adapter for permanent gassing and or the calibration of transmitters with electrochemical sensors (not type AC), catalytic sensors (pellistors) and transmitters of type Polytron IR CO₂ and Polytron IR Ex HC. Also suitable for continuous use in connection with a sampling unit.
Order No.: 68 06 978



ST-5695-2006

Test gas ampoules

For use with the calibration bottle.

Related Products



ST-3812-2003

Dräger Polytron® 7000

The Dräger Polytron® 7000 is a gas detector that can satisfy many toxic and oxygen gas measurement applications on a single platform. It meets the requirements of the compliance market as well as the high specification requirements of customised solutions.



D-86378-2013

Dräger Polytron® 2000

Robust, precise, safe – the Dräger Polytron® 2000 is a stationary gas detector for measuring standard gases (O₂, H₂S, NH₃, Cl₂, CO). With the new, pre-calibrated DrägerSensor MEC and robust design, this gas transmitter is a reliable and economic solution for non-explosion proof areas.

Technical Data

Type	Intrinsically safe transmitter for electrochemical sensors	
Gases and Ranges	Toxic gases and oxygen in various ranges	
Output	Analog	4 to 20 mA
	Maintenance signal	3.4 mA constant
	Fault signal	< 3.2 mA
Power Supply	12 to 30 VDC, 2-wire	
Ambient Conditions	Transmitter only, for sensors see separate sensor data sheet	
	Temperature	- 40 to + 65 °C / - 40 to + 150 °F
	Pressure	700 to 1300 mbar / 20.7 to 38.4 inch Hg
	Humidity	0 to 100 %RH, non condensing
Enclosure	IP 66 / 67, NEMA 4, GRP housing, M20 cable gland	
Dimensions (approx.)	166 x 135 x 129 mm / 6.54" x 5.32" x 5.08" (H x W x D)	
Weight (approx.)	900 g / 2 lbs.	
Approvals	ATEX	II 1G Ex ia IIC Ga T4/T6 - 40 °C to + 65/ + 40 °C
		II 3G Ex ic IIC Gc T4/T6 - 40 °C to + 65/ + 40 °C
		I M1 Ex ia I Ma - 40 °C to 65 °C
	IECEX	Ex ia IIC T4/T6 Ga - 40 °C to + 65 / + 40 °C
		Ex ic IIC T4/T6 Gc - 40 °C to + 65 / + 40 °C
		Ex ia I Ma - 40 °C to 65 °C
	UL	Class I, Div 1, Group A, B, C, D
		Class II, Div 1, Group E, F, G
		T6/T4: - 40 to + 40 / + 65 °C
	CSA	Class I, Div 1, Group A, B, C, D
Ex ia T6/T4: - 40 to + 40 / + 65 °C		
CE mark	electromagnetic compatibility (2004/108/EG)	

Gas

Ammonia	Boron Trichloride	Butadiene
Carbon Monoxide	Chlorine	Diborane
Diethyl Ether	Ethylene Oxide	Germane
Hydrazine	Hydrofluoric Acid	Hydrogen
Hydrogen Chloride	Hydrogen Cyanide	Hydrogen Sulfide
Isopropanol	Nitrogen Dioxide	Nitrogen Monoxide
Oxygen	Ozone	Phosphine
Propylene	Sulfur Dioxide	Tetrahydrofurane

For other gases ask our system centers

Ordering Information

Dräger Polytron 3000 with Display	Various
Dräger Polytron 3000 without Display	Various
Polytron Dockingstation, one per transmitter	83 17 990
Duct Mount Kit	83 17 150

Notes

Notes

Not all products, features, or services are for sale in all countries.
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

REGION DACH

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd.
25 International Business Park
#04-20/21 German Centre
Singapore 609916
Tel +65 6308 9400
Fax +65 6308 9401
asia.pacific@draeger.com

REGION CENTRAL AND SOUTH AMERICA

Dräger Panama S. de R.L.
Complejo Business Park,
V tower, 10th floor
Panama City
Tel +507 377-9100
Fax +507 377-9130
contactcsa@draeger.com

Locate your Regional Sales
Representative at:
www.draeger.com/contact

