

Dräger Polytron® Pulsar 2 Detection of flammable gases and vapours

The Dräger Polytron Pulsar 2 is the latest infrared technology in open path gas detection. Equipped with all the same functions as the standard Dräger Pulsar, Pulsar 2 is fitted with an ABS moulded cover and is supplied with either a junction box or certified connector to provide complete flexibility during installation.



Benefits

Easy adjustment and commissioning

Designed for one man installation and commissioning through use of a hand-held terminal the Pulsar 2 transmitter and receiver can be accurately aligned, gas level zeroed and commissioned with maximum efficiency. The factory calibration of the Polytron Pulsar 2 makes manual setting and test gas superfluous.

System stability

The detector is designed so that no fault remains undetected. During normal operation, the output signal is between 4 to 20 mA, depending on the measured gas concentration. A signal of < 1 mA represents a fault due to a constant beam block or hardware failure requiring immediate attention. However, a signal of 2 mA identifies a beam block and will go to fault if this persists for more than 60 minutes. The Pulsar will also output a 3.5 mA signal to indicate pre-warning where the optics may be dirty or miss-aligned. During the period which the Pulsar displays 'Pre-warning' it will still detect gas allowing the customer to schedule maintenance on the detector therefore reducing down time. With no unrevealed faults, the Pulsar 2 is SIL 2 capable.

In-built database

The receiver logs records and details a report of the last seven working days and a summary of the last 32 weeks. These reports contain important information such as measuring values, i.e. 'beam block', gas readings, warning signals, signal strength, adjustments, supply voltage and operating temperature.

Extensive access to data from safe areas

The optional Polytron Pulsar Software can provide easy access to configuration, current measured values and the internal data-logger from a non-hazardous area through Digital Communication. For large and complex installations, the Pulsar software can allow integration of several devices via the AI5000. Up to 32 AI500's can be multi dropped; therefore allowing access to up to 128 pulsars - useful for planning service and maintenance measures.

High performance

The Pulsar receiver communicates to the transmitter via a digital link which allows the receiver to identify and adjust to fluctuating environmental conditions. The microprocessor built into the receiver unit instructs the transmitter unit to increase the flash rate for increased performance and accuracy. The Pulsar is immune to influences such as sunlight, gas flares, arc welding or resonance effects due to vibrations of rotating parts, as well as to environmental influences such as mist, drizzle or snow. The flash rate is also increased upon the detection of gas to ensure both accuracy and fast response.

Heated optics

Regulated internal lens heaters protect against build up of ice and snow under adverse weather conditions. They also prevent condensation on the lenses eliminating interference with the measurement function.

Benefits

HART-communication

The HART-Communication of the Polytron Pulsar allows for digital communication between the explosion-proof and the secure areas. Without additional cabling, you can obtain real-time access to the status of individual detectors and to the configuration and historical data of each device.

Worldwide Approvals

The Polytron Pulsar Duct Mount holds a performance approval from FM, and global product approvals including ATEX, IECEx, CSA and UL.

System Components



D-6806-2016

Dräger REGARD® 7000

The Dräger REGARD® 7000 is a modular and therefore highly expandable analysis system for monitoring various gases and vapours. Suitable for gas warning systems with various levels of complexity and numbers of transmitters, the Dräger REGARD® 7000 also features exceptional reliability and efficiency. An additional benefit is the backward compatibility with the REGARD®.



ST-335-2004

Dräger REGARD®-1

The Dräger REGARD®-1 is a standalone, self contained single channel control system for the detection of Toxic, Oxygen and Ex hazards. The control system is fully configurable for a single input from either a 4 to 20 mA transmitter or a Dräger Polytron® SE Ex measuring head.

System Components



Dräger REGARD® 3900

The Dräger REGARD® 3900 is a standalone, self contained control system for the detection of Toxic, Oxygen and Ex hazards. The control system is fully configurable between 1 and 16 channels, depending upon the type and quantity of input/output boards installed.

Accessories



Alignment and test kit

Alignment kit with hand held terminal, gas test cards and software with case. For alignment and function test.
Order No.: 23 50 325



AI500 digital interface

Digital interface for remote access to up to four Pulsars.
Order no: 23 50 306

Related Products



D-49077-2012

Dräger Flame 5000

The Dräger Flame 5000 is an imaging based explosion proof flame detector. This visual flame detection system uses digital image processing and advanced algorithms to process and interpret flame characteristics. This principle offers an extended field of view and fewer false alarms. Each detector is equipped with a colour CCTV camera.



ST-11659-2007

Dräger PIR 7000

The Dräger PIR 7000 is an explosion proof point infrared gas detector for continuous monitoring of flammable gases and vapours. With its stainless steel SS 316L enclosure and drift-free optics this detector is built for the harshest industrial environments, e.g. offshore installations.



D-14579-2010

Dräger Polytron® 5700 IR

The Dräger Polytron® 5700 IR is a cost effective explosion-proof transmitter for the detection of flammable gases in the lower explosive limit (LEL). It uses a high performance infrared Dräger PIR 7000 sensor that will quickly detect most common hydrocarbon gases. A 3-wire 4 to 20-mA analogue output with relays makes it compatible with most control systems.



ST-8821-2005

DrägerSensor® IR

Upgrade from catalytic bead to infrared technology with ease using the DrägerSensor® IR. The Sensor IR can replace catalytic ex-sensors (pellistors) from the majority of manufacturers without replacing controllers, cables, junction boxes or control systems.

Technical Data

Type	Explosion proof Open Path gas detector utilizing dual wavelength infrared absorption technic	
Gases	Wide range of hydrocarbons including the alkane series from methane to hexane, propylene, ethanol and methanol	
Range	From 0 to 4 up to 0 to 8 LEL*m	
Factory calibration	Methane or propane, selectable. Other hydrocarbon gases on request	
Operating distance	4 to 60 m, 30 to 120 m or 100 to 200 m, 13 to 197 ft, 98 to 394 ft or 328 to 656 ft separation of transmitter and receiver	
Signal output	Analog	Measuring 4 to 20 mA
	Pre-warning	3.5 mA, dirty optics or misalignment
	Beam block	2 mA
	Fault	<1 mA
	Digital	HART
Supply Voltage	ATEX	18 to 30 VDC
	UL, CSA	18 to 27 VDC
Power Consumption	Max. 0.95 A @ 24 V, with full heating and all source lamps operating	
Response time t_{95}	<2 s	
Ambient conditions	Temperature	-40 to +60 °C, -40 to +140 °F
	Pressure	800 to 1,100 hPa, 23.6 to 32.5 inch Hg
	Humidity	0 to 100 %RH, non-condensing
Enclosure	IP66, stainless steel	
Size (W x H x D, approx.)	260 x 340 x 220 mm, 10.25" x 13.3" x 8.5", each	
Weight (approx.)	6 kg, 12.2 lbs, each	
Approvals	ATEX	II 2GD Ex d [ia] IIC T6/T5, -40 to +40 / +60 °C
	IECEx	Ex d [ia] IIC T6/T5, -40 to +40 / +60 °C
	FM/ANSI	FM ANSI/FM 6325, ANSI/ISA-12. 13-04
	DNV	A-12526
	IEC 60079-29-4	Tested by FM Approvals
	UL	Class I, Div 1, Group C, D
	CSA, NRTL/C	Class I, Div 1, Group C, D

Ordering Information

Dräger Polytron® Pulsar 2 – variations by max. operating range and approval – transmitter and receiver, each fitted with an ABS moulded cover.

Supplied with EEx e junction box or EEx d certified plug and socket.

Dräger Polytron® Pulsar 2 Accessories	Part number
Junction Box Dräger Polytron® Pulsar 2 ATEX	23 50 298
AI500 Digital Interface Unit for Dräger Polytron® Pulsar 2	23 50 306
Dräger Polytron® Pulsar 2 Remote Junction Box/HHT Kit	23 50 322
Dräger Polytron® Pulsar 2 Alignment Kit, ATEX/CSA	23 50 325
Adapter AI500 to HHT or PC	23 50 326
Dräger Polytron® Pulsar 2 PC Software with cable (supports Pulsar, AI500 and HHT)	23 50 327
Attenuator plate AP800	23 50 339
ABS Moulded Cover	23 50 510

Ordering Information

Dräger Polytron® Pulsar 2 with ABS moulded cover and Ex e certified junction box	Part number
Dräger Polytron® Pulsar 2 ATEX 4–120 m (RX only Ethylene)	23 50 340
Dräger Polytron® Pulsar 2 ATEX 100–200 m (RX only Ethylene)	23 50 341
Dräger Polytron® Pulsar 2 ATEX 4–60 m (TX only)	23 50 499
Dräger Polytron® Pulsar 2 ATEX 30–120 m (TX only)	23 50 500
Dräger Polytron® Pulsar 2 ATEX 100–200 m (TX only)	23 50 501
Dräger Polytron® Pulsar 2 ATEX 4–120 m (RX only)	23 50 502
Dräger Polytron® Pulsar 2 ATEX 100–200 m (RX only)	23 50 503
Dräger Polytron® Pulsar 2 with ABS moulded cover and Ex d certified plug and socket connectors	Part number
Dräger Polytron® Pulsar 2 ATEX 4–120 m (RX only Ethylene)	23 50 342
Dräger Polytron® Pulsar 2 ATEX 100–200 m (RX only Ethylene)	23 50 343
Dräger Polytron® Pulsar 2 ATEX 4–60 m (TX only)	23 50 504
Dräger Polytron® Pulsar 2 ATEX 30–120 m (TX only)	23 50 506
Dräger Polytron® Pulsar 2 ATEX 100–200 m (TX only)	23 50 507
Dräger Polytron® Pulsar 2 ATEX 4–120 m (RX only)	23 50 508
Dräger Polytron® Pulsar 2 ATEX 100–200 m (RX only)	23 50 509

Notes

Not all products, features, or services are for sale in all countries.
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

REGION DACH

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd.
25 International Business Park
#04-20/21 German Centre
Singapore 609916
Tel +65 6308 9400
Fax +65 6308 9401
asia.pacific@draeger.com

REGION CENTRAL AND SOUTH AMERICA

Dräger Panama S. de R.L.
Complejo Business Park,
V tower, 10th floor
Panama City
Tel +507 377-9100
Fax +507 377-9130
contactcsa@draeger.com

Locate your Regional Sales
Representative at:
www.draeger.com/contact

